

**ARI - Wastewater - Combination Air Valves
Application and Sizing Chart**



Model	D-025	D-025-L	2" / D-26	3" / D-26	4" / D-26	6" / D-26	8" / D-26
Body Material	Nylon or SS	Nylon or SS	Nylon or SS	Nylon or SS	Stainless	Stainless	Stainless
Weight	10 lbs / 32 lbs	15 lbs / 28 lbs	20 lbs / 36 lbs	34 lbs / 60 lbs	105 lbs	200 lbs	315 lbs
Height	18"	22"	22"	25"	35"	36"	47"
Outlet	1.5"	1.5"	2"	3"	4"	6"	8"
Max Working Pressure	150 PSI	250 PSI	250 PSI	250 PSI	250 PSI	250 PSI	250 PSI
A/V Air Flow (CFM)	125	125	500	1,200	2,100	5,000	9,200
Pump Station	NO	YES	YES	YES	YES	YES	YES
Force Main	YES	YES	YES	YES	YES	YES	YES
Line Size (ROT)*	12" Or Smaller	12" Or Smaller	12"-24"	14"-48"	30"-54"	42"+	54"+
<i>*Rule of Thumb Estimate</i>							
Max Flow GPM (ROT)*	935	935	3,740	8,976	15,708	37,400	68,816
<i>*Rule of Thumb Estimate</i>							

Clinton Office
601-924-5522
ms-sales@mmgonline.net

McIntire Management Group

Kansas City Office
816-746-6669
kc-sales@mmgonline.net