



ONE coupling per nominal diameter joins most DWV pipe materials:

- | | |
|----------------------------|-----------------|
| Steel | Stainless Steel |
| ABS/PVC Plastic (SCH 40) | Copper |
| Cast Iron | Duriron® |
| Extra Heavy Cast Iron | Ductile Iron |
| Thinwall Plastic (SDR 35) | Clay |
| Asbestos Cement (Transite) | |

For non-pressure, gravity flow sewer applications only.

SIZE	DESCRIPTION	O.D. RANGE
2"	MAX DWV 2	1.63" - 2.50"
3"	MAX DWV 3	3.00" - 4.13"
4"	MAX DWV 4	4.00" - 5.56"

U.S. Patents Pending



STOP THE GUESSWORK

The Only Universal Coupling for DWV Applications

Gripper Gasket LLC
 1660 Leeson Lane | Corona, CA 92879
 (951) 479-4999 | (951) 479-4997 Fax

18 ADVANTAGES at a GLANCE

No more trips to a job site with the wrong coupling.

Low inventory storage costs as only a few sizes are needed to meet all applications.

Increased efficiency equals labor cost savings.

Greatly exceeds hydrostatic testing requirements of ASTM C1173.

The reduction process takes place centrally, uniformly and separately on each side of the pipe coupling.

Robust design ensures the coupling won't fall apart on the job site.

Stainless steel tension bands ensure reliable, rapid and uniform assembly.

Multiple double sealing profile on each side.

A bedding channel on both sides of the tension bands ensures reliable and secure band guidance.

High impact polyamide (nylon) securing cage.

Securing cage and gasket retain a neutral position during the diameter adjustment process, which means that puckering or deformation of the rubber can be reliably avoided.

Corrosion resistant AISI 304 series stainless steel components.

Stepless adjustment on both sides, with permanent securing against significant shear loads and deflection.

The design of the tension bands ensure the force application during the diameter adaptation is spread evenly onto the pipe over the entire circumference.

Deflection is possible on each side, up to 3°.

No bushings are required to bridge even substantial diameter differences within the same nominal diameter.

Nominal I.D.'s match-up perfectly, whether same or different pipe materials.

Injection molded EPDM rubber gasket.

