



Product Information Sheet

Corrosion Resistant
AISI 304 Series
Stainless Steel
Components

Injection Molded
EPDM Gasket

High Impact
Polyamide (Nylon)
Securing Cage



**The Only Universal
Sewer Repair Coupling**

**ONE coupling per nominal
diameter joins:**

- Clay
- Ductile Iron
- Asbestos Cement
- Cast Iron
- Plastic

ONE coupling replaces six (6) couplings: 01, 02, 03, 51, 55 & 56 series!

SIZE	PART DESCRIPTION	O.D. RANGE
4"	MAX 4	4.13" - 5.56"
4"+	MAX 4 Oversize	4.21" - 5.90"
5"	MAX 5	5.30" - 6.50"
6"	MAX 6	6.27" - 7.75"
6"+	MAX 6 Oversize	6.27" - 8.10"
7"	MAX 7	7.20" - 8.80"
8"	MAX 8	8.40" - 10.15"
9"	MAX 9	9.63" - 11.13"
10"	MAX 10	10.50" - 12.68"
12"	MAX 12	12.50" - 15.00"
13"	MAX 13	13.00" - 15.75"
16"	MAX 16	16.34" - 19.10"

- *Quick and easy repair of most types and sizes of sewer/drainage pipes*
- *No more trips to a job site with the wrong coupling*
- *Increased efficiency equals labor cost savings*
- *Click-lock system ensures no damages or corrosion associated with spot welding*
- *Accommodates significant shear load and deflection*
- *Recommended installation torque of 80 in./lbs.*
- *For non-pressure, gravity flow sewer applications only*

Specifications: Exceeds the requirements of ASTM C1173 (Standard Specification for Flexible Transition Couplings for Underground Piping Systems). IAPMO 4224 listed.